PA series

D.A.S.

PA-4000



DESCRIPTION

The PA series amplifiers are designed and built to provide an affordable, quality powering solution. The wide range of models makes the series ideal for both installed or mobile sound reinforcement applications.

The amplifiers incorporate a rugged 2 unit all-steel chassis ensuring structural rigidity. The low-noise fans offer both quiet and cool operation. The amplifier incorporates rear located switches which permit, operational mode selection (bridge, stereo or parallel) and input sensitivity selection.

KEY FEATURES

- · Input Sensitivity Selector
- \cdot 2100 W x 2100 W at 4 Ω
- · Stereo/Bridged/Parallel Operation
- · SpeakON output connectors
- · Clip, protection and signal present LED indicators

APPLICATIONS

- · Live sound reinforcement
- · Bands, DJ's and performers
- · Speech and vocals
- · Music playback in entertainment
- \cdot A/V, conferences and presentations

SPECIFICATIONS

Output Power Ratings		
Power 8 Ohms, Both Channels Driven	2 x 1400 W	
Power 8 Ohms Bridged	4250 W	
Power 4 Ohms, Both Channels Driven	2 x 2100 W	
Electronics and Connectors		
Amplifier Channels	2	
Frequency Response	20 Hz - 20 kHz, +0 - 1 dB	
Total Harmonic Distortion	<0.5% , 20 Hz - 20 kHz	
Signal to Noise Ratio	> 100 dB @ 20 Hz - 20 kZ	
Voltage gain	37 dB	
Damping Factor	> 200 @ 10 Hz - 400 Hz	
Controls	Power On/Off, Gain Pots	
Cooling	Internal heat sinks with forced air: Fan cooled	
Amplifier Protections	Protection against short circuits, no-load, on/off muting, RF interference.	
LED Indicators	Power, Protection, Signal, Clip	
Audio Signal Input Connector	2 x Female XLR	
Audio Signal Loop Thru Connector	2 x Male XLR	
Speaker Output Connector	2 x speakON	
AC Input Connector	IEC	
Operating Range	180-250 VAC	
Current Draw 230 V	15.2 A	



Dimensions-Weight

Dimensions (H x W x D)	88 x 482 x 294 mm 3,5 x 19,0 x 11,6 in	
Net Weight	19,5 kg (43,0 lb)	
Shipping		
Carton Dimensions (H x W x D)	160 x 580 x 540 mm 6,3 x 22,8 x 21,3 in	
Shipping Weight	21.0 kg (46.2 lb.)	

ORDERING INFORMATION

Performance				
Model	Description	P/N		
System				
PA-4000		10717140		

DIMENSIONS



