

SUB 702-AS II

ACTIVE SUBWOOFER

DESCRIPTION

Housing a 12" woofer, the SUB 702-AS II, is a very compact active sub enclosure and features a 1400 W powerful digital amplifier. It is the ideal complement to 8" or 10" speakers, creating small but powerful satellite systems with outstanding performance. Thanks to its compact size it can easily be carried and is very quick and easy to start using the built-in digital stereo crossover (DSP) with adjustable crossover frequency to connect the satellite.



FEATURES

- 1400 Watt Digital Amplifier
- 12" Woofer, bass reflex housing
- Stereo crossover
- Switchable crossover frequencies
- Phase-reverse switch
- Electronic equalization, soft limiter and protection
- Stereo XLR input, Stereo XLR signal output



TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response:	40 Hz ÷ 120 Hz
	Max SPL @ 1m:	129 dB
Transducers	Woofers:	12", 2.5" v.c
Input/Output section	Input signal:	bal/unbal
	Input connectors:	XLR
	Output connectors:	XLR
	Input sensitivity:	-2 dBu/+4 dBu
Processor section	Hi-Pass Frequencies:	110 Hz
	Low-Pass Frequencies:	80 Hz
	Protections:	Thermal, RMS
	Limiter:	Soft Limiter
	Controls:	Volume, EQ, Phase, Xover
Power section	Total Power:	1400 W Peak, 700 W RMS
	Low frequencies:	1400 W Peak, 700 W RMS
	Cooling:	Convection
	Connections:	VDE
Standard compliance	CE marking:	Yes
Physical specifications	Cabinet/Case Material:	Baltic birch plywood
	Handles:	2 Side
	Pole mount/Cap:	Yes
	Color:	Black
Size	Height:	487 mm / 19.17 inches
	Width:	354 mm / 13.94 inches
	Depth:	498 mm / 19.61 inches
	Weight:	19 kg / 41.89 lbs
Shipping informations	Package Height:	524 mm / 20.63 inches
	Package Width:	536 mm / 21.1 inches
	Package Depth:	400 mm / 15.75 inches
	Package Weight:	22.4 kg / 49.38 lbs

PART NUMBER

- **13000454**
 - SUB 702-AS II
 - 115V
 - EAN 8024530012922
- **13000453**
 - SUB 702-AS II
 - 220-240V
 - EAN 8024530012847

SUB 702-AS II

