



MILAN S.r.l. a socio unico

Head Office – Export department:

Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione

Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it



Technical Datasheet

tasker® C506 – 6x0,12 mm² - Spiral Shielded Cable



NOTE CATEGORY APPLICATIONS

The picture does not represent the real number of conductors
Shielded Multipolar Cable (See Data Network Catalogue)
Data transmissions, electronics and alarm systems.

- A:** Grey Soft **PVC** Sheath. RAL 7032
Outer cable diameter Ø 4,60 (±0,10) mm.
- B:** Spiral Shielding O.F.C. Red Copper covering 100%.
- C:** Cores Insulation with Soft PVC. DIN 47100 Standards..
Cores Diameter Ø 0,90 (±0,10) mm.
- D:** Stranded O.F.C. Red Copper formation 7x0,15 mm.
Nom. Cross section 6x0,12 mm².

MARKING CUSTOM PRODUCTION

tasker® C506 6x0,12 LOW VOLTAGE COMPUTER CABLE MADE IN ITALY
This product may be custom produced also in **LSZH, PE, PUR**,
with or without Metallic Armor.

Cable Properties

Conductor Resistance	140 Ω/Km
Capacity Core/Core	90 pF/m
Capacity Core/Shield	180 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 15.02.18
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated