



## Prestel VCS-S1

Hi-Fi Speaker



[DATASHEET](#)

# Hi-Fi Speaker



Powerful Speaker

Hi-Fi

Hi-Fi



Multiple Mounting Options

Hi-Fi speaker specifically designed for large conference room settings. It utilizes digital decoding technology to achieve 5.1 channel audio playback, delivering a more immersive and realistic sound experience. With its built-in high-power speaker, it can provide ample volume to cover the entire venue.



## FEATURES

### ▼ PICKS UP VOICES AT EVERY SEAT

With the 5.1 channel audio mode, ensures even and immersive sound coverage in every corner of the room, creating an immersive meeting experience.

### ▼ TRUE-TO-LIFE SOUND REPRODUCTION

By breaking away from conventional echo wall designs, effectively reduces noise and distortion, allowing participants to hear the most authentic sound quality.

### ▼ PROFESSIONAL AUDIO TUNING FOR BALANCED SOUND

The speaker's audio is professionally tuned by sound engineers, delivering deep and rich bass, full mid-range, and clear high tones, providing a comfortable listening experience.

### ▼ EASY DEPLOYMENT AND EFFORTLESS MOUNTING

Can be placed on a tabletop or mounted on the wall, offering flexibility to meet the installation requirements of different conference rooms.

## SPECIFICATIONS

### ▼ SPEAKER

Rated Output Power	(10W + 15W) x 2 (+/- 0.5 dB, 10% THD)
Speaker Impedance	4Ω
Frequency Response	110Hz - 16kHz / ±3 dB
Loudness	50dB SPL @ 1W, 95dB SPL @ 7.5W
Signal-to-noise Ratio	≥65dB
Total Harmonic Distortion	200Hz - 300Hz < 2.5% 300Hz - 10kHz < 1% @ 7.5W

### ▼ GENERAL SPECIFICATION

Input Voltage	DC 18V
Input Current	2A
Operating Temperature	-10°C ~ 40°C
Storage Temperature	-40°C ~ 60°C
Power Consumption	30W
MTBF	>30000H
Main Unit	408.5mm x 73mm x 90mm
Secondary Unit	402.5mm x 73mm x 90mm
Dimension	805mm x 73mm x 90mm
Weight	1.5kg
Product Certification	CE, GS, CB, FCC, ETL, SAA, RCM, PSE

### ▼ INTERFACE

Audio Input	1x Line In, 3.5mm Audio Interface
RCA	1x RCA, Dual Channel, (Connect the sub-speaker)
Power	DC 18V

### ▼ INSTALLATION MODE

Stationary Type	Wall Mounting, Hanging Mounting
Combined Type	Split Mounting, Stack Mounting



## INTERFACE

- 1 — DC IN
- 2 — AUX
- 3 — RCA, Connect the sub-speaker
- 4 — RCA, Connect the main-speaker

