

HD 3216

PLASTIC HORN SPEAKER WITH DRIVER

DESCRIPTION

The HD 3216 are compact, lightweight and watertight horn speakers. They are designed to provide high efficiency and characterized by the high intelligibility of the reproduced sound with low distortion. The built-in line transformer makes it possible to connect the horn loudspeaker to both 70 and 100 V constant voltage lines, and select the delivered power by means of a rotary dial on the rear cover



FEATURES

- Hi-pass filter for protecting driver against out-of-range low-freq
- IP 66 construction for indoor-outdoor environmental temperature between -25°C to +70°C
- UV-stabilized autoextinguishing UL-HB ABS plastic
- Colour RAL 7035
- Stainless-Steel mounting hardware

TECHNICAL SPECIFICATIONS

Acoustical specifications	Frequency Response (-10dB):	250 Hz ÷ 10000 Hz
	Max SPL @ 1m:	122 dB
	Horizontal coverage angle:	130°
	Vertical coverage angle:	60°
	System Sensitivity:	108 dB
<hr/>		
Power section	Nominal Impedance (ohm):	8 ohm
	Power Handling:	25 W RMS
	Peak Power Handling:	100 W PEAK
	Recommended Amplifier:	50 W
<hr/>		
Transducers	Compression Driver:	1.5"
<hr/>		
Input/Output section	Input connectors:	Cable
	Output connectors:	Cable
<hr/>		
Standard compliance	IP protection grade:	IP 66
	CE marking:	Yes
<hr/>		
Physical specifications	Cabinet/Case Material:	ABS
	Hardware:	Stainless steel U bracket
	Color:	Grey - RAL 7035
<hr/>		
Size	Height:	170 mm / 6.69 inches
	Width:	315 mm / 12.4 inches
	Depth:	295 mm / 11.61 inches
	Weight:	1.45 kg / 3.2 lbs
<hr/>		
Shipping informations	Package Height:	305 mm / 12.01 inches
	Package Width:	325 mm / 12.8 inches
	Package Depth:	190 mm / 7.48 inches
	Package Weight:	2.61 kg / 5.75 lbs

PART NUMBER

- **13133039**

HD 3216

EAN 8024530001223

DRAWINGS

