



400W LED Follow Spot Light

User Manual

FOLLOWSPOT PRO 400



First of all, welcome to use the LED400 DMX high-efficiency follow spot light. For your safety and better use of the light, please read the instructions carefully before use and operate in accordance with the prescribed procedures to avoid misuse endangering personal safety and damaging the lamp.

A. Product introduction:

The LED400 DMX high-efficiency follow spot light is made of high-quality aluminum profiles and high-quality carbon conductive iron. It adopts the latest shape design and good optical system, plus 5 powerful fans, good heat dissipation, high brightness, and the LED light source turns on and off. 0-100 dimming precision and smoothness and various changes of color temperature, manual focusing plus linear focusing, fast focal length update, this lamp adopts general international DMX512 signal, can be used alone or in connection with an external console or laptop. The console equipped with the machine can set the master and follower at will, two superimposed color films, separate 5 colors + white light color change, plus three color temperature films (3200K, 4500K, 5600K, 6500K) effect, adjustable aperture, 1 second 7 times strobe effect + dimming function.

B. Instructions for use:

After opening the packing box, carefully check whether the lamp is damaged due to transportation, such as whether the screw is loose or whether the lens is burst: After checking that everything is normal, choose a suitable location. The computer board will perform a self-check for about 40 seconds, and the operation can be performed after the self-check is completed ..

C. Operate according to the instructions on the buttons on the console.

Connect the signal cable to the main board for automatic conversion and use DMX control, and directly operate on the main control panel without connecting the signal, which is very simple and easy to operate.

The 127 number of the first fader is the stroboscopic speed effect above the dimming value 0-100%.

The second 3 color temperature film 3200K 4500K 6500K + atomization effect

The third push rod is the focus push rod, slowly moving until the aperture is clearest.

The fourth fader is the aperture size fader: adjust to a value above 127 for the automatic aperture zoom function

The six blue buttons on the right are color buttons. Each button represents a color.

C. Technical Parameters:

Frequency: 50Hz-60Hz Dynamic system: 4 powerful fans

Voltage: 110V-240V Working environment: indoor

Total power: 550W strobe 1-7 times per second

Signal: standard international DMX512 signal

Protection level: IP22

Wooden box packing size: 1080x470x580mm, lamp weight 47KG,

Air box packing size: 1080x670x530mm Weight: 32KG


Operation function; aperture size. Strobe effect. Change the color. focusing.

Color: 5 colors plus white light red, yellow, blue, green, rose red. 3 kinds of heating film + atomization.


Beam angle: 8-15 degrees

Features: This new product. nice appearance. Easy to operate. High brightness and long range. Small size and light weight. Mechanical control, good stability, widely used in bars, wedding banquets. The ideal choice for large-scale performances.

D. Safety instructions:



Avoid electric shock



Bulb high fever

1. Before repairing, please consult a qualified repair station.
2. When installing and repairing the lamp, please make sure that the power supply of the lamp body is in the off position
3. Please do not use other different specifications of power supply, voltage and laser type
4. Do not look directly at the light source of the lamp, so as not to damage your eyes

| No. | Menu | Function | Description |
|-----|-----------|-------------------------------|--|
| 1 | | | |
| 2 | C1-C6 | C1 C2 C3 C4 C5 C6 | Press the six colors corresponding to the six buttons |
| 3 | L000-L255 | Brightness and strobe setting | Push the first fader (0-127) to adjust the brightness from dark to bright |
| 4 | F000-F255 | Color wheel 2 adjust | Push the second push rod to adjust the color wheel two |
| 5 | E000-E255 | Focus adjust | Push the third fader to adjust the focus |
| 6 | O000-O255 | Aperture adjust | Push the fourth fader to adjust the aperture (0-127) to adjust the aperture size, (128-256) aperture zoom back and forth |

DMX512 CHANNEL

| Address | Function | Description |
|---------|---------------|---|
| CH1 | Dimming | (0-255)dimming.Linear dimming, from dark to bright |
| CH2 | Strobe | (0-255)Stroboscopic speed can be adjusted from slow to fast |
| CH3 | Color wheel 1 | (0-255) corresponds to six colors on average |
| CH4 | Color wheel 2 | (0-255) corresponds to six colors on average |
| CH5 | Focusing | Adjust the focus |
| CH6 | Aperture | Aperture adjustment (0-122) to adjust the size of the aperture; (123-256) the aperture to zoom back and forth |

