

MC 910

Condenser Microphone

Order # 499.986



FEATURES

- Omnidirectional polar pattern
- Switchable pre-attenuation -15 dB
- Slight treble boost
- Phantom power 11 - 52 V

APPLICATIONS

This true condenser microphone provides an enormous versatility due to its neutral sound and accurate design. The features of the MC 910 include the wide frequency response of 30 - 20,000 Hz and a signal-to-noise ratio of 69 dB.

The MC 910 is suitable as a main microphone for stereo and surround recordings as well as close miking of voice or individual instruments. Its subtle treble boost provides an open and natural sound even with larger distances. It also compensates for off axis high frequency attenuation of the omnidirectional capsule. Due to the switchable pre-attenuation of 15 dB it is suitable for use with very high sound pressure levels. The switchable low-cut filter with 6 dB/octave below 250 Hz provides a reproducible audio variant. With the WS 101 wind shield, the MC 910 can be used for speech and vocals. The MC 910 is phantom powered (11 - 52 V) and therefore suitable for live or studio applications.

OPTIONAL ACCESSORIES

BMC 05 FM	Standard microphone cable XLR-XLR, 5 m long	Order # 434.787
BMC 10 FM	Standard microphone cable XLR-XLR, 10 m long	Order # 434.795
EA 19/25	Elastic suspension 19 - 25 mm, incl. MKV 11 microphone clamp	Order # 407.194
GST 400	Microphone stand, 3/8", height 0.90 - 1.65 m, with G 400 boom	Order # 421.294
GST 500	Microphone stand, 3/8", height 0.85 - 1.60 m, with telescopic G 500 boom	Order # 406.252
MAV 800	Clip for hanging mounting of microphones	Order # 448.133
MAV 802	Multi-purpose mounting for two microphones	Order # 453.323
WS 101	Wind shield, charcoal-grey	Order # 111.244
WS 53	Wind shield, small, charcoal-grey	Order # 436.607

MC 910

TECHNICAL SPECIFICATIONS

Transducer type True condenser
Operating principle Pressure
Frequency response 30 - 20,000 Hz
Polar pattern Omnidirectional
Open circuit voltage
at 1 kHz (0 dB = 1 V/Pa) 25 mV/Pa = -32 dBV
Nominal impedance 180 Ω
Load impedance 1000 Ω
Max. SPL at 1 kHz 127 dB
with pre-attenuation 142 dB
Signal-to-noise ratio rel. to 1 Pa 69 dB

A-weighted equivalent SPL 18 dB
Low-cut filter switchable, 6 dB/octave
at 250 Hz
Power supply 11 - 52 V phantom
power
Current consumption 4.6 mA
Connector 3-pin XLR male
Dimensions:
Length 128 mm
Diameter 21 mm
Weight without cable 115 g

FREQUENCY RESPONSE & POLAR PATTERN

This frequency response curve (measuring tolerance ± 2 dB) and polar pattern correspond to a typical production sample for this microphone.

