# ACTION 500<sup>series</sup>



# ACTION-M512



### DESCRIPTION

ACTION-M512 is a passive stage monitor designed to deliver a highly versatile solution, from fixed installations to the popular portable PA application. Its rotatable horn with  $80^{\circ} \times 50^{\circ}$  dispersion means the enclosure can also be used as a PA system.

As part of our company culture, all our systems are developed under a single philosophy: to deliver the highest possible quality in terms of both materials and overall system design. In the ACTION-500 series we use the same birch plywood as our touring systems for a tight, nautral warm sound found nowhere else on the market.

For long-term optimal performance of the ACTION-500 passive versions, the system can only be a complete sound system when rounded out with our amplifiers and processors with stored presets and limiters.

## **KEY FEATURES**

- Passive two-way stage monitor
- $\cdot$  Birch plywood enclosure
- $\cdot$  Durable ISO-flex paint
- Recommended processor: DSP-226
- $\cdot$  Recommended amplifier: PA series

## **APPLICATIONS**

- · Live sound reinforcement
- Bands, DJ's and performers
- Speech and vocals
- $\cdot$  Music playback in entertainment
- $\cdot$  A/V, conferences and presentations

# SPECIFICATIONS

#### Performance

Periornance	
Frequency Range (-10 dB)	63 Hz – 20 kHz
Horizontal Coverage (-6 dB)	80°
Vertical Coverage	50°
Nominal Impedance	8 ohms
RMS Power Handling	300 W
Peak Power Handling	1200 W
On-axis Sensitivity 1W/l m	95 dB SPL
Maximum Peak SPL at 1 m	130 dB
Recommended Amplifier	PA-1500
Recommended Processor	DSP-226
Connectors	
Audio Input Connector	1 x speakON NL4
Audio Output Connector	1 x speakON NL4
Enclosure	
Enclosure Construction	Birch Plywood
Enclosure Geometry	Trapezoidal
Finish	ISO-flex Paint
Color	Black
Depth	450 mm (17,7 in)
Dimensions ( H x W x D )	335 x 650 x 450 mm 13,2 x 25,6 x 17,7 in
Net Weight	17,5 kg ( 38,5 lb )
II	



# ACTION-M512

### Components

LF Driver	12MI
HF Driver	M-34
Horn/Waveguide	BC-85

## Shipping

Carton Dimensions ( H x W x D )	383 x 747 x 503 mm 15,1 x 29,4 x 19,8 in
Shipping Weight	18,6 kg ( 40,9 lb )

# **ORDERING INFORMATION**

Performance		
Model	Description	P/N
System		
System ACTION-M512	2-way Passive Point Source	10427243
	,	
Replacement Parts		
12MI	Cone Transducer	10214310
BC-85	Horn	30003946
F-ACTM512	Filter	30009292
GM-12MI	Recone Kit	20208290
GM-M34	Diaphragm	20205060
M-34	Compression Driver	10207080
Accessories		
FUN-ACTM12	Transport Accessories	10103530
SPK4-1	Electronic Accessories	20502000
SPK4-10	Electronic Accessories	20502001
SPK4-20	Electronic Accessories	20502002
TRD-6	Installation & Stacking Acc.	10104470
TRD-7	Installation & Stacking Acc.	10104471
TRPD-S2-PAK	Installation & Stacking Acc.	10104011

## DIMENSIONS



