


NTG-3

Precision Broadcast-Grade Shotgun Microphone

AUSTRALIA
107 Carnarvon st, Silverwater NSW 2128 Australia
Ph: +61 2 9648 5855 Fx: +61 2 9648 2455

USA
PO Box 91028, Long Beach CA 90809-1028
Ph: +1 562 364 7400 Fax: +1 888 412 4664



Incl. Accessories

- Water resistant aluminium storage cylinder (RCNTG3)
- Wind shield (WSNTG3)
- Zip pouch (ZP2)
- Microphone clip (RM5)


Features

- Designed to withstand adverse environmental conditions
- 50% less self-noise than the majority of shotgun microphones
- Extremely low handling noise
- High level of immunity to radio frequency interference
- True Condenser (external RF biased)
- High Sensitivity
- Superior broadcast sound quality
- Designed and manufactured in Australia
- Full 10 year warranty with online registration


Specifications

Acoustic Principle	Line Gradient
Directional Pattern	Super-Cardioid
Frequency Range	40Hz ~ 20,000Hz
Sensitivity	-30dB \pm 2dB re 1V/Pa @ 1kHz
Nominal Impedance	25 Ω
Equivalent Noise	13dBA SPL (A - weighted per IEC651)
Maximum Output	+8.2dBu (@ 1% THD into 1k Ω)
Dynamic Range	117dB (per IEC651)
Maximum SPL	130dB (@ 1kHz, 1% THD into 1k Ω load)
Signal/Noise	81dB SPL (A - weighted per IEC651)
Power Req.	48V Phantom Power (44-52V min 5mA)
Dimensions	Length - 255mm Diameter - 19mm
Output Connection	3 pin XLR, balanced output between Pin 2 (+), Pin 3 (-) and Pin 1 (ground)
Net Weight	163g

Polar Pattern



Frequency Response



RØDE
MICROPHONES